



5SX Miniature Circuit Breakers

Selection

IEC AC/DC Version 5SX5^① and 5SX6^①

Description	Ordering Information
IEC maximum AC ratings 5SX5: 250/415V AC 5SX6: 250/440V AC IEC maximum DC ratings 5SX5: 1 pole—220V DC; 2 pole—440V DC 5SX6: 60V DC per pole	▶ Select Circuit Breaker based on number of poles, rated current and desired trip curve characteristics see page 772. ▶ Accessories see page 771. ▶ Technical Data see pages 772-773. ▶ Dimensions see page 774.

5SX5 Miniature Circuit Breakers^①

Illustration	Description	Amp Rating	C Curve Catalog No	B Curve Catalog No	Price \$
	One Pole	0.5	5SX5105-7	—	90.
		1	5SX5101-7	—	90.
		1.6	5SX5115-7	—	90.
		2	5SX5102-7	—	90.
		3	5SX5103-7	—	90.
		4	5SX5104-7	—	90.
		6	5SX5106-7	5SX5106-6	90.
		8	5SX5108-7	—	90.
		10	5SX5110-7	5SX5110-6	90.
		13	5SX5113-7	5SX5113-6	90.
		16	5SX5116-7	5SX5116-6	90.
		20	5SX5120-7	5SX5120-6	90.
		25	5SX5125-7	5SX5125-6	90.
		32	5SX5132-7	5SX5132-6	90.
		40	5SX5140-7	5SX5140-6	90.
		50	5SX5150-7	5SX5150-6	90.
	Two Pole	0.5	5SX5205-7	—	180.
		1	5SX5201-7	—	180.
		1.6	5SX5215-7	—	180.
		2	5SX5202-7	—	180.
		3	5SX5203-7	—	180.
		4	5SX5204-7	—	180.
		6	5SX5206-7	5SX5206-6	180.
		8	5SX5208-7	—	180.
		10	5SX5210-7	5SX5210-6	180.
		13	5SX5213-7	5SX5213-6	180.
		16	5SX5216-7	5SX5216-6	180.
		20	5SX5220-7	5SX5220-6	180.
		25	5SX5225-7	5SX5225-6	180.
		32	5SX5232-7	5SX5232-6	180.
		40	5SX5240-7	5SX5240-6	180.
		50	5SX5250-7	5SX5250-6	180.

5SX6 Miniature Circuit Breakers^①

Illustration	Description	Amp Rating	C Curve Catalog No	B Curve Catalog No	Price \$
	One Pole	40	5SX6140-7	5SX6140-6	180.
		50	5SX6150-7	5SX6150-6	180.
		63	5SX6163-7	5SX6163-6	180.
		80	5SX6180-7	—	180.
		100	5SX6191-7	—	180.
		125	5SX6192-7	—	180.
	Two Pole	40	5SX6240-7	5SX6240-6	361.
		50	5SX6250-7	5SX6250-6	361.
		63	5SX6263-7	5SX6263-6	361.
		80	5SX6280-7	—	361.
		100	5SX6291-7	—	361.
		125	5SX6292-7	—	361.
	Three Pole	40	5SX6340-7	5SX6340-6	541.
		50	5SX6350-7	5SX6350-6	541.
		63	5SX6363-7	5SX6363-6	541.
		80	5SX6380-7	—	541.
		100	5SX6391-7	—	541.
		125	5SX6392-7	—	541.
	Four Pole	40	5SX6440-7	5SX6440-6	721.
		50	5SX6450-7	5SX6450-6	721.
		63	5SX6463-7	5SX6463-6	721.
		80	5SX6480-7	—	721.
		100	5SX6491-7	—	721.
		125	5SX6492-7	—	721.

①Not UL/CSA. For DC applications observe polarity marking on terminal area.